



# 48.5" Strip-Type LCD Monitor (2k)

FT485MOB



- 2K Quad HD Resolutions - 1920×360 (strip-type)
- High Quality LCD Monitor - vertical or horizontal use
- Anti-glare surface treatment (chemical etching)
- Optically bonded glass panel to LCD panel
- No moving parts inside - long lifetime guaranteed
- Numerous fixation possibilities for easy integration
- High quality LED backlight panels
- Integrated audio speakers (2×3W)
- 2 years guarantee (24/7 usage)






faytech's strip-type monitor has a modern edge-to-edge sleek look with its LCD front panels. The device has a wide variety of video connectors, an opening on the back with cover for connectors and power supply, as well as a complete embedded design that makes it perfect for integration.

This device has a solid and light-weight aluminum casing with numerous fixation possibilities makes it easy to integrate into any enclosure or rack. Additionally, the solution comes with a fanless heat dissipation system, which allows reliable 24/7 operation.

This device is the perfect choice for a wide variety of applications, including digital signage, way-finding, office automation and in areas like shopping malls, retail stores, hotels, hospitals and many more. Lastly, a wide variety of customizations are also available to better fit your needs, including touch functionality and docking to third-party systems, among others.



Legend / Notes	
Applicable to version 1	(v1)
Applicable to version 2	(v2)
Applicable to all Versions	None



<b>Product name</b>				<b>48.5" Strip-type LCD Monitor (2K)</b>			
<b>Article code / EAN number</b>				<b>FT485MOB</b>			
Global Article Code	European Article Code	Release date (DIMY)	Version*	Global Article Code	European Article Code	Release date (DIMY)	Version*
3030513434	-	01/03/2022	v1				

<b>IP rating</b>	
IP65 front / IP40 back	

<b>LCD Panel</b>	
Screen diagonal (Inch/cm)	48.5/121.92
Display active screen size (cm)	120.96×22.68
Aspect ratio	48:9
Physical resolution	1920×360
Colours displayed	16.7M
Brightness (cd/m <sup>2</sup> )	500
Contrast	4000:1
Typical reaction time Tr/ Tf (ms)	8/8
Visual Angle horizontal/vertical (°)	178/178
Backlight / Backlight Lifetime (hours)	LED / 30,000



<b>External Connectors</b>	
Video	1x HDMI 1.4
	1x DP
	1x VGA
Audio	1x Audio-out
Connector	1x 24V DC-IN
Sensor	1x IR receiver (for remote)

<b>Glass Panel</b>	
Surface Hardness	7H
Surface Treatment	Anti-glare (chemical etching)
Glass Strengthening	Physically Strengthened

<b>Operation / Mechanical</b>	
Operating Temperature (°C)	-10 ~ +60
Humidity Range (RH)	10% - 90%
Net weight (kg)	12.05
Gross weight (kg)	15.05 (incl. cartonage)
Housing material	Aluminum
Housing (mm) L x W x H	279.0 x 48.0 x 1262.0
Mounting	See drawing (VESA 75 & others)

<b>Power</b>	
Power Supply	100-240V ACDC active switching; 24V DC-Out
Working Power (W)	24
Power Consumption (W)	27
Stand-By Consumption (W)	<1

<b>Included in the Delivery</b>	
Power Supply (see Power section)	
HDMI Cable	
Remote Controller (IR)	



Tolerance: ± 1.5mm

Errata and technical modifications reserved

## Update Notes:

\* Only the latest version can be ordered, previous versions are only for historic reference.

### Version:

### Changes:

v1

-

First version

## Corporate Headquarters

### faytech AG

Bischhäuser Aue 10  
37213 Witzenhausen  
Germany

[support@faytech.com](mailto:support@faytech.com)  
[contact@faytech.com](mailto:contact@faytech.com)  
[www.faytech.com](http://www.faytech.com)

China: +86 755 8958 0612  
Germany: +49 5542 30374 10  
USA: +1 646 843 0877  
India: +91 11 49707436  
Japan: +070 4127 5167  
Korea: +82 10 3479 1815